## New Construction Energy Code Compliance Certificate

Date Certificate Posted

Per R401.3 Certificate. A building certificate shall be posted on or in the electrical dist	Plymouth				
Mailing Address of the Dwelling or Dwelling Unit	City		Plymouth		
Name of Residential Contractor	MN Lice	ense Number	Adding Quality to Life		

THERMAL ENVELOPE								$\neg$	RAD	ON CONTROL SYSTEM			
THE CHARLEST E			Type: Check All That App					hat A	\pply			Passive (No Fan)	
			<b> </b>	1	<u> </u>	0.00.		1					Active (With fan and manometer or
			0 86							ene			other system monitoring device)
			ype	<u>a</u>						styr		Locati	on (or future location) of Fan:
			all T	Sabl	_		Foam, Closed Cell	  -	<u>r</u>	, oly	Ф		,
			of of	pplir	lowi	atts			boa	ed F	urat		
			Total R-Value of all Types of Insulation	Non or Not Applicable	Fiberglass, Blown	Fiberglass, Batts	Sec	Foam Open Cell	Mineral Fiberboard	Rigid, Extruded Polystyrene	Rigid, Isocynurate		
Insulation Location			Total R-Va	ž	lass	lass	ŏ	ò	аFi	Ext	180		
			sula	o nc	oerç	Serç	Jam	am	ner	gid,	gid,		
			오프	ž	芷	芷	Ъ.	Ъ	≅	Ř	شَ	Other	w
Below Entire Slab													
Foundation Wall							Щ			Щ	_		
Perimeter of Slab on Grade													
Rim Joist (1st Floor)				Щ			Ш		Щ	Щ	_		
Rim Joist (2nd Floor+)													
Wall													
Ceiling, flat													
Ceiling, vaulted											_		
Bay Windows or cantilevered areas													
Floors over unconditioned area				ш	ш		Ш		ш	ш			
Describe other insulated areas				_	חוני	+ sv	stem	oir.	+iah(	nass	· (cf	m/100	
Building envelope air tightness (ACH):  Duct system air tightness (cf. sf):								, (Сі	111/100				
Windows & Doors Heating or Cooling Duct						uct	s Outs	ide Conditioned Spaces					
					icabl	e, all	duc	ts locat	ed in conditioned space				
Solar Heat Gain Coefficient (SHGC):													
MECHANICAL SYSTEMS						Make	-up Air Select a Type						
Appliances	Heatin	g System	Domestic Water Heater			r	С	ooli	ng S	vster	m		
							Cooling System					<b> </b>	Not required per mech. code
First Time													Db/a
Fuel Type												<b> </b>	Passive
Manufacturer												<b> </b>	Powered
													Interlocked with exhaust device.
Model													Describe:
	Input in BTUS:		Capacity in Gallons:		_		Outp Tons			_			Other, describe:
Rating or Size	AFUE or		Gallorio.				SEEF					Locat	on of duct or system:
Efficiency	HSPF%						/EER					Looa	off of duct of System.
	Heatir	ng Loss	Heati	ng C	3ain		(	Cool	ing l	Load	一	i	
Residential Load Calculation		-5	+								$\dashv$	╟──	
			<u> </u>									<u> </u>	Cfm's
													" round duct OR
MECHANICAL VENTILATION	ON SYS	ГЕМ					_						" metal duct
Describe any additional or combine	d heating o	r cooling sys	stems if inst	alled	: (e.c	ı. two	ი furr	nace	s or	air		Comb	oustion Air Select a Type
source heat pump with gas back-up	-				. (	,	•		• .				Not required per mech. code
Select Type			_						Passive				
			: Low:				High	High:				Other, describe:	
Heat Recover Ventilator (HRV)	Capacity i	n ctms:	LOW.			High:		_	_		$\overline{}$	Location of duct or system:	
			Low:				High	1:	ļ			Locati	on of duct or system:
Heat Recover Ventilator (HRV)	V) Capacity						High	า:	<u></u>			Locati	on of duct or system:
Heat Recover Ventilator (HRV) Energy Recover Ventilator (ER	V) Capacity						High	า:	<u></u>		_	Locat	on of duct or system:  Cfm's
Heat Recover Ventilator (HRV) Energy Recover Ventilator (ER Balanced Ventilation capacity in	V) Capacity n cfms:	/ in cfms:					High	n:				Locat	