


9 TON STREETS BASED ON PROJECTED TRAFFIC ARE EQUIVALENT TO OR GREATER THAN THE STANDARDS HEREIN SPECIFIED.

CONCRETE SIDEWALKS SHALL BE A MINIMUM OF 6 INCHES (6") THICK AT ALL DRIVEWAYS.

MINIMUM SECTION DETAIL A



MATERIAL	SPECIFICATIONS	G.E. FACTORS
BITUMINOUS WEAR COURSE	2360	2.25
BITUMINOUS BINDER & BASE	2360	2.25
AGGREGATE BASE	CL.5 (3138)	1.00
AGGREGATE SUBBASE	CL.3, CL.4 (3138)	0.75
SELECT GRANULAR MATERIAL	3149	0.50

DESIGN CRITERIA

8 AGG. BASE CLASS 3 MIN/DOT SPEC. 3130
(100% CRUSHED)

12" SELECT GRAN. BORROW SPEC. 3149.2B2
GEOTEXTILE FILTER FABRIC TYPE V
(IF REQUIRED)

APPROVED SUBGRADE

PRESENT ADT=1000 VPD (MIN.)
ANNUAL GROWTH FACTOR=3.0%
20 YEAR DESIGN PERIOD
DESIGN SPEED IS 30 MPH, UNLESS
OTHERWISE NOTED BY CITY
MIN. \sum N18₂₀ = 150,000